## NSN 5962-01-081-4888

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-081-4888

Body Length:	
0.440 inches	
Body Width:	
Between 0.245 inches and 0	0.285 inches
Body Height:	
Between 0.045 inches and (	0.085 inches
Maximum Power Dissipati	on Rating:
516.0 milliwatts	
Operating Tempurature Ra	inge:
-55.0/+125.0 degrees celsiu	S
Storage Tempurature Ran	ge:
65.0/+150.0 degrees celsiu	S
Features Provided:	
Hermetically sealed and mo	nolithic and positive outputs and schottky and delay, d-type and edge triggered and w/enable
nclosure Material:	
Ceramic and glass	
nclosure Configuration:	
Flat pack	
Output Logic Form:	
Fransistor-transistor logic	
nput Circuit Pattern:	
3 input	
Design Function And Qua	ntity:
flip-flop, d-type	
Case Outline Source And	Designator:
-5 mil-m-38510	
Terminal Surface Treatme	nt:
Gold	
Voltage Rating And Type	Per Characteristic:
5.5 volts power source	
Precious Material And Loc	ation:
Terminal surface gold	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-m-38510 specific	ation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
-	al catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	nce requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quant	
16 flat leads	
Specification Data:	
81349-mil-m-38510/71 gove	rnment specification
Shelf Life:	

N/a

## NSN 5962-01-081-4888

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

