NSN 5962-01-081-9695

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-081-9695

Body Length:	
0.785 inches	
Body Width:	
Between 0.220 inches	nd 0.310 inches
Body Height:	
Between 0.140 inches	nd 0.185 inches
Maximum Power Diss	pation Rating:
670.0 milliwatts	
Operating Tempuratu	e Range:
-55.0/+125.0 degrees o	elsius
Storage Tempurature	Range:
-65.0/+150.0 degrees o	elsius
Features Provided:	
Hermetically sealed an	monolithic and positive outputs and medium speed
nclosure Material:	
Ceramic and glass	
nclosure Configurati	n:
Dual-in-line	
nput Circuit Pattern:	
3 input	
Design Function And	Quantity:
3 driver, line	
Case Outline Source	Ind Designator:
0-1 mil-m-38510	
Ferminal Surface Trea	tment:
Solder	
/oltage Rating And T	pe Per Characteristic:
6.0 volts power source	
Fime Rating Per Chao	eristic:
350.00 nanoseconds p	ropagation delay time, low to high level output and 650.00 nanoseconds propagation delay time, high to low level
output	
Test Data Document:	
97942-635a750 drawin	(this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specificat	on, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Q	antity:
14 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	