## NSN 5962-01-082-4215

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-082-4215

## **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 164.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/enable and w/buffered output and w/disable and low power and schottky and asynchronous and w/clear **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 shift register, parallel out, serial **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Test Data Document:** 97942-583r500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A458a0