NSN 5962-01-082-4226

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psp/5062-01-082-4226

view Online at https://aerobasegroup.com/nsn/5962-01-062-4226
Body Length:
Between 0.745 inches and 0.785 inches
Body Width:
Between 0.300 inches and 0.325 inches
Body Height:
Between 0.055 inches and 0.140 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/strobe
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 driver, liquid crystal
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.5 volts power source
Time Rating Per Chacteristic:
800.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay time, high to low level
output
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

A458a0

Yes - demil/mli