## NSN 5962-01-082-5515

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-082-5515

View Online at https://aerobasegroup.com/nsn/5962-01-082-5515
Body Length:
Between 0.337 inches and 0.360 inches
Body Width:
Between 0.235 inches and 0.265 inches
Body Height:
Between 0.050 inches and 0.080 inches
Maximum Power Dissipation Rating:
19.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Countermeasures set, type an/alq-137
Features Provided:
Hermetically sealed and monolithic and positive outputs and schottky and w/totem pole output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
8 input
Design Function And Quantity:
1 gate, nand power
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
6.00 nanoseconds propagation delay time, low to high level output and 7.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-082-5515

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0