## NSN 5962-01-082-5566

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-082-5566 **Body Length:** Between 0.750 inches and 0.785 inches **Body Width:** Between 0.245 inches and 0.271 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/storage and programmable and programmed and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic

## Time Rating Per Chacteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

## Test Data Document:

**Input Circuit Pattern:** 

49956-461442 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## Shelf Life:

6 input

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0