NSN 5962-01-082-6340



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-082-6340 **Body Length:** Between 0.740 inches and 0.780 inches **Body Width:** Between 0.240 inches and 0.270 inches **Body Height:** Between 0.135 inches and 0.165 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and programmable and adjustable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 9 input **Design Function And Quantity:** 1 demodulator and 1 modulator **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 26.0 volts power source **Time Rating Per Chacteristic:** 20.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0