

View Online at <https://aerobasegroup.com/nsn/5962-01-082-7027>

**Body Length:**

0.700 inches

**Body Width:**

0.250 inches

**Body Height:**

Between 0.140 inches and 0.180 inches

**Maximum Power Dissipation Rating:**

300.0 milliwatts

**Operating Temperature Range:**

+0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and externally compensated and negative outputs and positive outputs and high gain and programmable and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

4 channel

**Design Function And Quantity:**

1 amplifier, operational, general purpose

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

45.0 volts power source

**Time Rating Per Characteristic:**

1500.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

05869-710205 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0