NSN 5962-01-082-9979

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-082-9979
Body Length:
Between 0.750 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.295 inches
Body Height:
Between 0.140 inches and 0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Radar set, type an/apn-221
Features Provided:
Hermetically sealed and monolithic and positive outputs and edge triggered and low power and retriggerable and w/buffered output and
w/storage
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
12 input
Design Function And Quantity:
1 register, storage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.5 volts power source
Time Rating Per Chacteristic:
1100.00 nanoseconds propagation delay time, low to high level output and 1100.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-082-9979

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0