NSN 5962-01-083-2249

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-083-2249
Body Length:
Between 2.030 inches and 2.080 inches
Body Width:
Between 0.515 inches and 0.600 inches
Body Height:
0.205 inches
Maximum Power Dissipation Rating:
1.5 watts
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Wsd: ground mobile force satellite comm term (an/tsc-93a); spruance class dd (963); virginia class cgn (41); landing craft air cushion
(lcac); radar set, lightweight ed (an/tps-59); los angeles class ssn (688); over the horizon back scanner (oth-b) program (an/fps-118);
ticonderoga class cg (47); sturgeon class ssn (637); kilauea class t-ae26
Features Provided:
Hermetically sealed and static operation and programmable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Metal oxide-semiconductor logic
Input Circuit Pattern:
38 input
Criticality Code Justification:
Feat
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Memory Device Type:
Ram
Special Features:
Weapon system essential
Terminal Type And Quantity:
40 printed circuit
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-083-2249

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0