

View Online at <https://aerobasegroup.com/nsn/5962-01-084-3665>

**Body Outside Diameter:**

Between 0.350 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

830.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

F-15; helicopter, advance attack, ah-1w; virginia class cgn (41); helicopter, uscg search and rescue, hh-60j; sturgeon class ssn (637); los angeles class ssn (688); helicopter, seach and rescue, hh-60h; nimitz class cvn; helicopter, carrier based asw, sh-60f; tarawa class lha; 2m/ate microminiaature automatic test equipment

**Features Provided:**

High precision

**Inclosure Material:**

Metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

4 input

**Design Function And Quantity:**

2 comparator, voltage

**Terminal Surface Treatment:**

Solder

**Product Name:**

Low power low offset voltage dual comparators

**Voltage Rating And Type Per Characteristic:**

-18.0 volts power source and 18.0 volts power source

**Terminal Type And Quantity:**

8 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0