## NSN 5962-01-084-8714

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-084-8714

## **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -65.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and high reliability and medium speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, and **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.0 volts power source **Time Rating Per Chacteristic:** 420.00 nanoseconds propagation delay time, low to high level output and 320.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 10001-3242726 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a Unit Of Measure:

Demilitarization:

Yes - demil/mli

## NSN 5962-01-084-8714

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

