NSN 5962-01-084-9465

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-084-9465 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 605.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and synchronous and edge triggered and w/enable and w/clear **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 1 shift register, bidirectional and 1 shift register, universal **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -1.5 volts power source and 5.5 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 16 flat leads **Specification Data:** 81349-mil-m-38510/076 government specification Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-01-084-9465

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0