NSN 5962-01-085-0373

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-085-0373 **Body Length:** 0.870 inches **Body Width:** Between 0.220 inches and 0.280 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 730.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and negative outputs and positive outputs and w/strobe **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 3 input **Design Function And Quantity:** 2 receiver, line **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 20.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 80249-911635 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

A458a0

Yes - demil/mli