NSN 5962-01-085-0533

Digital Microcircuit - Page 1 of 1

1 latch

Solder

16 flat leads

Shelf Life:

Unit Of Measure:

Demilitarization: Yes - demil/mli

N/a

Fiig: A458a0

Terminal Surface Treatment:

Terminal Type And Quantity:

5.5 volts power source **Test Data Document:**

Voltage Rating And Type Per Characteristic:



View Online at https://aerobasegroup.com/nsn/5962-01-085-0533 **Body Length:** Between 0.370 inches and 0.410 inches **Body Width:** Between 0.245 inches and 0.283 inches **Body Height:** Between 0.030 inches and 0.090 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** Countermeasures set, type an/alq-13 (v) **Features Provided:** Hermetically sealed and monolithic and positive outputs and presettable and resettable and delay, d-type and low power **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).