## NSN 5962-01-085-3466

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-085-3466

Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.240 inches and 0.260 inches
Maximum Power Dissipation Rating:
600.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+175.0 degrees celsius
End Application:
Radar surveillance set, type no. An/aps-94f
Features Provided:
Monolithic and hermetically sealed and negative outputs and positive outputs and w/buffered output
Inclosure Material:
Glass and metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 amplifier, reference
Case Outline Source And Designator:
T0-5 joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Time Rating Per Chacteristic:
200000.00 nanoseconds propagation delay time, low to high level output
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5962-01-085-3466

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0