NSN 5962-01-085-5114

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-085-5114

| view Online at http | s.//aerobasegroup.com/nsn/5962-01-065-5114 |
|-----------------------|--|
| Body Length: | |
| 0.840 inches | |
| Body Width: | |
| Between 0.220 incl | nes and 0.310 inches |
| Body Height: | |
| Between 0.140 incl | nes and 0.185 inches |
| Maximum Power I | Dissipation Rating: |
| 165.0 milliwatts | |
| Operating Tempu | rature Range: |
| -55.0/+125.0 degre | es celsius |
| Storage Tempurat | ure Range: |
| -65.0/+150.0 degre | es celsius |
| Features Provided | 1 : |
| Hermetically sealed | and monolithic and negative outputs and high speed |
| Inclosure Material | : |
| Ceramic and glass | |
| Inclosure Configu | ration: |
| Dual-in-line | |
| Output Logic Forr | n: |
| Emitter-coupled log | ,ic |
| Input Circuit Patte | ern: |
| Triple 2 input | |
| Design Function | And Quantity: |
| 3 gate, exclusive, | or/nor |
| Case Outline Sou | rce And Designator: |
| D-2 mil-m-38510 | |
| Terminal Surface | Treatment: |
| Solder | |
| Voltage Rating Ar | nd Type Per Characteristic: |
| 5.2 volts power so | urce |
| Test Data Docume | ent: |
| 81349-mil-m-38510 |) specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes c | ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and | performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type An | d Quantity: |
| 16 printed circuit | |
| Specification Data | 1: |
| 81349-mil-m-38510 |)/60 government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| Demilitarization: | |
| | |
| Yes - demil/mli | |

NSN 5962-01-085-5114

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

