

View Online at <https://aerobasegroup.com/nsn/5962-01-085-6678>

**Body Length:**

Between 0.750 inches and 0.780 inches

**Body Width:**

Between 0.245 inches and 0.275 inches

**Body Height:**

Between 0.140 inches and 0.160 inches

**Maximum Power Dissipation Rating:**

93.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Radar surveillance set, type an/aps-94f

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and asynchronous and low power and w/enable and w/clear

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

9 input

**Design Function And Quantity:**

1 counter, ripple

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

80063-sm-a-942622 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli



**Fiig:**

A458a0