

View Online at <https://aerobasegroup.com/nsn/5962-01-085-6689>

**Body Length:**

0.790 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Training set, tactical electronic warfare, type no. An/mst-t1

**Features Provided:**

Monolithic and hermetically sealed and positive outputs and medium speed and low power and w/complement and negative edge triggered and edge triggered and true/complementary and retriggerable and resettable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

8 input

**Design Function And Quantity:**

1 multivibrator, monostable

**Terminal Surface Treatment:**

Gold

**Voltage Rating And Type Per Characteristic:**

18.5 volts power source

**Time Rating Per Characteristic:**

900.00 nanoseconds propagation delay time, low to high level output

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0