NSN 5962-01-086-0303

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-086-0303 **Body Length:** Between 0.750 inches and 0.790 inches **Body Width:** Between 0.265 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.165 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -10.0/+80.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and 3-state output and expandable and w/decoded output and w/enable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 450.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Ram **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-086-0303

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0