## NSN 5962-01-086-2515

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-086-2515

View Online at https://aerobasegroup.com/nsn/5962-01-086-2515
Body Length:
0.496 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
800.0 milliwatts
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/open collector
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 driver, peripheral
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
10001-3279449 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

Fiig: A458a0

Yes - demil/mli