NSN 5962-01-086-6686

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-086-6686

Body	Length:

Between 0.660 inches and 0.785 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

Between 0.140 inches and 0.180 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Range finder-target designator, laser, type no. An/avq-25

Features Provided:

Monolithic and hermetically sealed and positive outputs and medium speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Quad 1 input

Design Function And Quantity:

4 driver, line

Case Outline Source And Designator:

T0-116 joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

16.0 volts power source

Time Rating Per Chacteristic:

200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

27014-m-78c29j/883b drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-086-6686

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0