NSN 5962-01-086-9587

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-086-9587

| View Online at https://aerobasegroup.com/nsn/5962-01-086-9587 |
|--|
| Body Length: |
| Between 0.745 inches and 0.770 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| Between 0.115 inches and 0.180 inches |
| Maximum Power Dissipation Rating: |
| 630.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and hermetically sealed and negative outputs and positive outputs |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| Dual 2 input |
| Design Function And Quantity: |
| 2 amplifier, operational, general purpose |
| Case Outline Source And Designator: |
| -0-001-ab joint electron device engineering council |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 26.0 volts power source |
| Test Data Document: |
| 80063-sm-a-949421 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 14 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli