NSN 5962-01-087-0223

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-087-0223 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.130 inches and 0.185 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Training set, tactical electronic warfare, type no. An/mst-t1 **Features Provided:** Monolithic and hermetically sealed and 3-state output and low power and schottky and w/enable and w/buffered output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 5 input **Design Function And Quantity:** 4 driver, line **Terminal Surface Treatment:** Gold or tin **Time Rating Per Chacteristic:** 150.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 81755-c10731 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

A458a0

Yes - demil/mli