

View Online at <https://aerobasegroup.com/nsn/5962-01-087-0912>

Body Length:

Between 0.750 inches and 0.785 inches

Body Width:

Between 0.245 inches and 0.271 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

400.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Monolithic and hermetically sealed and positive outputs and w/buffered output

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, and

Time Rating Per Characteristic:

45.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

34148-4081bmqb drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0