NSN 5962-01-087-2317

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-087-2317 **Body Length:** Between 0.365 inches and 0.385 inches **Body Width:** Between 0.365 inches and 0.385 inches **Body Height:** Between 0.060 inches and 0.070 inches **Maximum Power Dissipation Rating:** 276.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and low power and w/decoded output and w/enable and 3-state output and **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 15 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Ram **Memory Capacity:** Unknown **Test Data Document:** 82577-932775 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 flat leads Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5962-01-087-2317

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0