# NSN 5962-01-087-2325

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-087-2325

# **Body Length:**

Between 1.980 inches and 2.020 inches

# **Body Width:**

Between 0.570 inches and 0.600 inches

# **Body Height:**

Between 0.070 inches and 0.090 inches

# **Maximum Power Dissipation Rating:**

1.5 watts

#### **Operating Tempurature Range:**

-0.0/+70.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **End Application:**

Computer control, reference designator, u82

#### **Features Provided:**

Hermetically sealed and monolithic and bidirectional and w/enable and resettable and programmable and programmed and 3-state output

#### Inclosure Material:

Ceramic

### Inclosure Configuration:

Dual-in-line

# Output Logic Form:

N-type metal oxide-semiconductor logic

#### Input Circuit Pattern:

16 input

# **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

7.0 volts power source

# Time Rating Per Chacteristic:

30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level

output

# Memory Device Type:

Rom

#### **Special Features:**

Erasable

#### **Terminal Type And Quantity:**

40 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

# NSN 5962-01-087-2325

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

