## NSN 5962-01-087-3522

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-087-3522

| Body Length:  |
|---|
| Between 0.750 inches and 0.795 inches   |
| Body Width:   |
| Between 0.245 inches and 0.300 inches   |
| Body Height:  |
| Between 0.120 inches and 0.195 inches   |
| Operating Tempurature Range:  |
| -55.0/+125.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| Features Provided:  |
| Hermetically sealed and monolithic and positive outputs and bipolar and programmed and programmable and w/decoded output and            |
| expandable and high speed and w/buffered output and w/enable and w/disable  |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Output Logic Form:  |
| Transistor-transistor logic   |
| Input Circuit Pattern:  |
| 10 input  |
| Case Outline Source And Designator:   |
| -0-001-ag joint electron device engineering council   |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:   |
| 5.5 volts power source  |
| Time Rating Per Chacteristic:   |
| 70.00 nanoseconds propagation delay time, low to high level output  |
| Memory Device Type:   |
| Rom   |
| Memory Capacity:  |
| Unknown   |
| Test Data Document:   |
| 96214-2028233 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Terminal Type And Quantity:   |
| 16 printed circuit  |
| Shelf Life:   |
| N/a   |

Yes - demil/mli

**Unit Of Measure:** 

Demilitarization:

## NSN 5962-01-087-3522

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0