NSN 5962-01-087-5962

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-087-5962 **Body Length:** 0.870 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and negative outputs and positive outputs and medium speed and w/strobe **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 3 input **Design Function And Quantity:** 2 comparator, voltage, differential **Terminal Surface Treatment:** Silver **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 80.00 nanoseconds propagation delay time, low to high level output **Precious Material And Location:** Terminal surfaces silver **Precious Material:** Silver **Test Data Document:** 96214-800234 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-087-5962

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0