

View Online at <https://aerobasegroup.com/nsn/5962-01-087-5977>

Body Length:

Between 0.745 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.105 inches and 0.180 inches

Maximum Power Dissipation Rating:

480.0 milliwatts

Operating Temperature Range:

+0.0/+75.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and monolithic and positive outputs and w/enable and 3-state output and w/disable and programmable and programmed and schottky and expandable and w/decoded output and w/buffered output

Inclosure Material:

Plastic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

10 input

Case Outline Source And Designator:

-0-001-ac joint electron device engineering council

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output

Test Data Document:

55760-100142 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0