NSN 5962-01-087-6725

Linear Microcircuit - Page 1 of 1

Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-087-6725 **Body Width:** Between 0.335 inches and 0.370 inches **Body Height:** Between 0.165 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Teletypewriter set, type an/ugc-7 ()(v) **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and internally compensated **Inclosure Material:** Glass and metal **Inclosure Configuration:** Can **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 15.0 volts power source **Test Data Document:** 80063-sm-a-915728 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 8 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: