## NSN 5962-01-087-8520

Linear Microcircuit - Page 1 of 1

Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-087-8520 **Body Length:** 0.725 inches **Body Width:** 0.265 inches **Body Height:** Between 0.110 inches and 0.160 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Teletypewriter set, type an/ugc-7 ()(v) **Features Provided:** Hermetically sealed and monolithic and positive outputs and w/strobe **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 comparator, voltage **Terminal Surface Treatment:** Solder **Time Rating Per Chacteristic:** 400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 80063-sm-a-915733 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure: Demilitarization:**