NSN 5962-01-087-8525

Memory Microcircuit - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-087-8525 |
|---|
| Body Length: |
| Between 0.850 inches and 0.930 inches |
| Body Width: |
| Between 0.240 inches and 0.295 inches |
| Body Height: |
| Between 0.165 inches and 0.200 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and w/buffered output and |
| w/decoded output and w/enable |
| Inclosure Material: |
| Ceramic and glass |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 12 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 80.00 nanoseconds propagation delay time, low to high level output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Test Data Document: |
| 09344-34787 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 18 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig: A458a0

Yes - demil/mli