## NSN 5962-01-087-9496

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-087-9496

**Body Length:** 

Between 1.439 inches and 1.573 inches

**Body Width:** 

Between 0.990 inches and 1.050 inches

**Body Height:** 

Between 0.250 inches and 0.450 inches

**Maximum Power Dissipation Rating:** 

3.6 watts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**End Application:** 

Gyro magnetic compass set, type an/asn-1 ()

**Features Provided:** 

Hermetically sealed and monolithic and positive outputs

**Inclosure Material:** 

Glass and metal

**Inclosure Configuration:** 

Can

**Input Circuit Pattern:** 

1 input

**Design Function And Quantity:** 

1 regulator, voltage

**Case Outline Source And Designator:** 

Y mil-m-38510

**Terminal Surface Treatment:** 

Gold

**Voltage Rating And Type Per Characteristic:** 

15.0 volts power source

**Special Features:** 

Nuclear hardness critical item; no drawing to determine if isc code 1 item should be nuclear hardness. Can't change criticality code to reflect nuclear hardness

**Precious Material And Location:** 

Terminal surfaces gold

**Precious Material:** 

Gold

**Test Data Document:** 

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 pin

**Specification Data:** 

813/10-mil-m-38510/107 government enecification

## NSN 5962-01-087-9496

Linear Microcircuit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0