NSN 5962-01-087-9497

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-087-9497 **Body Length:** Between 0.850 inches and 0.930 inches **Body Width:** Between 0.240 inches and 0.295 inches **Body Height:** Between 0.165 inches and 0.200 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and w/enable and w/buffered output and w/decoded output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 5.5 volts power source **Time Rating Per Chacteristic:** 80.00 nanoseconds propagation delay time, low to high level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 09344-34820 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 18 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A458a0

Yes - demil/mli