

View Online at <https://aerobasegroup.com/nsn/5962-01-088-1021>

**Body Outside Diameter:**

Between 0.355 inches and 0.370 inches

**Body Height:**

Between 0.165 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

600.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Receiving set, countermeasures type an/alr-6 (v)

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and w/complement and w/strobe

**Inclosure Material:**

Glass and metal

**Inclosure Configuration:**

Can

**Input Circuit Pattern:**

4 input

**Design Function And Quantity:**

1 comparator, voltage, differential

**Terminal Surface Treatment:**

Tin

**Time Rating Per Characteristic:**

14.00 nanoseconds propagation delay time, low to high level output and 16.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0