

View Online at <https://aerobasegroup.com/nsn/5962-01-088-4257>

**Body Length:**

Between 0.376 inches and 0.384 inches

**Body Width:**

Between 0.245 inches and 0.271 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

800.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and high speed and high current

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

Dual 2 input

**Design Function And Quantity:**

2 driver, peripheral

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

8 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0