## NSN 5962-01-088-4912

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-088-4912

Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
Between 0.220 inches and 0.280 inches
Body Height:
Between 0.170 inches and 0.180 inches
Maximum Power Dissipation Rating:
128.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Transmitting set, radar data type an/akt-18
Features Provided:
Hermetically sealed and monolithic and positive outputs and w/enable and 3-state output
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
2 input
Design Function And Quantity:
4 transceiver
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
14.00 nanoseconds propagation delay time, low to high level output and 18.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
80063-sm-a-942623 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

## NSN 5962-01-088-4912

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0