NSN 5962-01-088-4913

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-088-4913

Body Length:

Between 1.980 inches and 2.020 inches

Body Width:

Between 0.585 inches and 0.615 inches

Body Height:

Between 0.080 inches and 0.105 inches

Maximum Power Dissipation Rating:

1.2 watts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+125.0 degrees celsius

End Application:

Transmitting set, radar data type an/akt-18b

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/enable and resettable and expandable and w/decoded output and w/storage

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

N-type metal oxide-semiconductor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

1 central processor unit

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Chacteristic:

100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Test Data Document:

80063-sm-a-942611 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

40 printed circuit

Shelf Life:

N/a

NSN 5962-01-088-4913

Digital Microcircuit - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0