NSN 5962-01-088-9777

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-088-9777

Body Length: 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1200.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and positive outputs and w/enable and medium speed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 8 channel **Design Function And Quantity:** 1 multiplexer, analog **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder or tin **Time Rating Per Chacteristic:** 1000.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 30003-810as474 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli

Fiig:

A458a0