

View Online at <https://aerobasegroup.com/nsn/5962-01-089-1812>

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Countermeasures set, type an/dlq-3b

Features Provided:

Hermetically sealed and monolithic and negative outputs and positive outputs

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

10 input

Design Function And Quantity:

1 converter, digital to analog

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

18.0 volts power source

Time Rating Per Characteristic:

375.00 nanoseconds propagation delay time, low to high level output and 375.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0