

View Online at <https://aerobasegroup.com/nsn/5962-01-089-8972>

Body Length:

Between 0.337 inches and 0.350 inches

Body Width:

Between 0.235 inches and 0.265 inches

Body Height:

Between 0.050 inches and 0.080 inches

Maximum Power Dissipation Rating:

195.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and positive outputs and w/enable and high speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

8 input

Design Function And Quantity:

1 shift register, parallel in, parallel out and 1 shift register, right shift, left shift and 1 shift register, serial in, parallel out

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

Time Rating Per Characteristic:

27.00 nanoseconds propagation delay time, low to high level output and 32.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

88818-a574a356 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0