## NSN 5962-01-090-0143

Microcircuit Set - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5962-01-090-0143        |
|--|
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius single hybrid                           |
| Storage Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| End Application:   |
| F16a/b   |
| Component Function Relationship:                                     |
| Unmatched  |
| Features Provided:   |
| Burn in and hybrid and tested to mil-std-883                         |
| Inclosure Material:  |
| Metal single hybrid  |
| Inclosure Configuration:   |
| Dual-in-line single hybrid   |
| Design Function And Quantity:  |
| 1 deglitcher single hybrid   |
| Terminal Surface Treatment:  |
| Gold err-100 err-100   |
| Product Name:  |
| Hybrid d/a converter assembly ultra low glitch, thick film           |
| Microcircuit Device Type And Quantity:                               |
| 2 hybrid   |
| Voltage Rating And Type Per Characteristic:                          |
| -18.0 volts power source err-100 and 18.0 volts power source err-100 |
| Precious Material:   |
| Gold   |
| Terminal Type And Quantity:  |
| 24 pin single hybrid   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

Yes - demil/mli

Fiig:

A458a0