# NSN 5962-01-090-0152

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-090-0152

# **Body Length:**

Between 0.250 inches and 0.260 inches

# Body Width:

Between 0.140 inches and 0.150 inches

# **Body Height:**

Between 0.036 inches and 0.050 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and monolithic and positive outputs and w/totem pole output

#### **Inclosure Material:**

Glass and metal

#### Inclosure Configuration:

Flat pack

## **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

Quad 2 input

# **Design Function And Quantity:**

4 gate, nor

# **Terminal Surface Treatment:**

Gold

# Voltage Rating And Type Per Characteristic:

-1.5 volts power source and 5.5 volts power source

# **Time Rating Per Chacteristic:**

60.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output

# Precious Material And Location:

Terminal surface gold

# Precious Material:

Gold

## **Test Data Document:**

88818-a574a176 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

14 flat leads

Shelf Life:

N/a

#### Unit Of Measure:

Demilitarization:

Yes - demil/mli

# **NSN 5962-01-090-0152** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

