NSN 5962-01-090-3459

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-090-3459

Body Length:
Between 0.755 inches and 0.785 inches
Body Width:
0.310 inches
Body Height:
Between 0.145 inches and 0.175 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and positive outputs and low power and schottky
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 5 input
Design Function And Quantity:
2 gate, nor
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A458a0