## NSN 5962-01-091-3033

Digital Microcircuit - Page 1 of 1

**Test Data Document:** 

Shelf Life:

**Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

N/a

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-091-3033 **Body Length:** Between 0.745 inches and 0.770 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.140 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Medium speed and burn in and hermetically sealed and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, or **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).