NSN 5962-01-091-5134

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-091-5134

Body Length: 0.840 inches

Between 0.220 inches and 0.310 inches

Body Height:

Body Width:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

300.0 milliwatts

Operating Tempurature Range:

+0.0/+75.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and programmable and high gain

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

4 channel

Design Function And Quantity:

1 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

10.0 volts power source

Time Rating Per Chacteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

00752-503140 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0