NSN 5962-01-092-5770

Hybrid Microcircuit - Page 1 of 2

5 flat leads



View Online at https://aerobasegroup.com/nsn/5962-01-092-5770

Body Length:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.130 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
An/alq-153
Features Provided:
Hybrid and hermetically sealed and burn in and positive outputs
Inclosure Material:
Metal
Inclosure Configuration:
Flat pack
Design Function And Quantity:
1 switch
Current Rating Per Characteristic:
40.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Gold
Product Name:
Switch, rf hybrid spst ^absorption^
Voltage Rating And Type Per Characteristic:
5.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds fall
Hybrid Technology Type:
Monolithic
Precious Material And Location:
Case and terminal surfaces gold
Precious Material:
Gold
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

NSN 5962-01-092-5770

Hybrid Microcircuit - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0