# NSN 5962-01-093-2700

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-093-2700

## **Body Length:**

Between 0.750 inches and 0.785 inches

## Body Width:

Between 0.245 inches and 0.271 inches

## **Body Height:**

Between 0.140 inches and 0.185 inches

## **Maximum Power Dissipation Rating:**

150.0 milliwatts

#### **Operating Tempurature Range:**

+0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic and positive outputs and low power and high speed

#### **Inclosure Material:**

# Ceramic and glass

Inclosure Configuration:

Dual-in-line

### **Output Logic Form:**

Emitter-coupled logic

#### Input Circuit Pattern:

11 input

#### **Design Function And Quantity:**

2 gate, and-or

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-8.0 volts power source

#### Time Rating Per Chacteristic:

3.50 nanoseconds propagation delay time, low to high level output and 3.50 nanoseconds propagation delay time, high to low level output

#### **Terminal Type And Quantity:**

16 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

Fiig:

A458a0