## NSN 5962-01-093-2701

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-093-2701 **Body Length:** 0.640 inches **Body Width:** Between 0.360 inches and 0.440 inches **Body Height:** Between 0.045 inches and 0.090 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and positive outputs and bipolar and programmable and programmed and schottky and w/open collector **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Gold Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Precious Material And Location:** Terminal surface gold **Precious Material:** Gold **Test Data Document:** 88818-a574a526 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

N/a

24 flat leads Shelf Life:

**Unit Of Measure:** 

**Terminal Type And Quantity:** 

## NSN 5962-01-093-2701

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0